

VIOSO®

Anystation Nano



fig. similar

Playback Performance	
Max. recommended resolution ¹ per output	FullHD
Max. content resolution ¹ (HAP playback)	2x UHD
Form Factor	
General Design	ultra portable desktop chassis
Dimensions (WxHxD mm)	180.3 x 35.6 x 182.9 mm
Weight	1.3 kg
Power Supply	external 230W
Application	
Warping & Blending	VIOSO 6
Auto Alignment	supported ²
Desktop Resolution Adaption	supported ³
Video Playback Solution	EXAPLAY
Operating System	Windows 10/11 IoT Enterprise LTSC
Hardware	
CPU	Intel Core i5, 6/12 Cores, 2.0/3.6 GHz Base/Turbo freq.
RAM	16 GB
GPU Primary	Intel UHD Graphics 630 <i>Display Connectors: 1 x Displayport 1.2, 1x HDMI 1.4</i>
GPU Secondary	NVIDIA Quadro T1000 8GB <i>Display Connectors: 4 x Mini Displayport 1.4 - adaptors required!</i>
Framelock / Genlock	-
HDD Primary	1 TB (OS+Data)
HDD Secondary	-
Waranty	
Software	2 years software maintenance
Hardware	2 years bring-in warranty
Interfaces	
USB	Front: 1x USB 3.2, 1x USB-C 3.2 Rear: 2x USB 3.2, 2x USB 3.1
Ethernet	1x 1 GB/s
Wireless	Wireless LAN Intel® Wi-Fi 6 AX201 2x2 AX Bluetooth® 5.1 or above
Audio	
Audio Interface	onBoard 7.1 Realtek ALC887
I/O	1x Stereo Jack 3.5 mm

¹ FullHD: 1920x1080@ 60Hz, WUXGA:1920x1200@60Hz, UHD:3840x2160@60Hz, 4K: 3840x2400Hz or 4096x2160@60Hz

² Supports camera based projector alignment; for supported cameras see <https://docs.vioso.com/preparation/camera>

³ This hardware supports highest level of OS integration for warping and blending (desktop resolution adaption)

Product Options

Anystation Nano

AN4-4

Adaptor Options

Mini Displayport to DVI, Displayport and HDMI - required for all Secondary GPU outputs!

Mini Displayport to DVI-D


Mini DisplayPort 1.2 to HDMI 2.0

Mini Displayport to Displayport

ADP_mDP-DVI

ADP_mDP-HDMI2

ADP_mDP-DP



VIOSO®

VIOSO GmbH | Ronsdorfer Straße 77a | 40233 Düsseldorf | Germany

info@vioso.com | www.vioso.com